

FormulaShell® 10W-40 Conventional Motor Oil

Conventional Motor Oil

Formula Shell® Motor Oil is formulated to provide wear protection and helps protect against the formation of sludge, varnish and rust.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

FormulaShell® SAE 10W-40 is a multigrade motor oil formulated to:

- Help reduce engine friction.
- Protect against the formation of sludge, varnish and rust.
- Protection against harmful deposits and acids, which aids in a clean running engine.

Main Applications

FormulaShell® SAE 10W-40 Conventional Motor Oil is recommended for use in all vehicles requiring the use of SAE 10W-40 viscosity grade engine oils under all driving conditions.

It can be mixed with other synthetic or mineral oils. Always consult your owner's manual for the correct viscosity grade and performance recommendation required for your vehicle.

Specifications, Approvals & Recommendations

Exceeds the requirements of the following industry specifications:

 API SN and all previous categories
For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk.

Always follow manufacturer's recommendations and specifications for viscosity grade and API service.

Typical Physical Characteristics

| Properties | | | Method | FormulaShell® Conventional Motor Oil |
|----------------------|--------|--------|------------|---|
| SAE Viscosity Grade | | | | 10W-40 |
| API Service Category | | | | SN |
| ILSAC | | | | - |
| Density | | kg/cm³ | ASTM D4052 | 869 |
| Flash Point | | °C | ASTM D93 | 200 |
| Pour Point | | °C | ASTM D97 | -33 |
| Viscosity | @40°C | mm²/s | ASTM D445 | 108.0 |
| Viscosity | @100°C | mm²/s | ASTM D445 | 15.7 |
| Viscosity Index | | | ASTM D2270 | 154 |
| CCS Viscosity | @-25°C | cP | ASTM D5293 | 6 210 |
| MRV Viscosity | @-30°C | cP | ASTM D4684 | 31 000 |

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shell representative.

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

Advice

Advice on applications not covered here may be obtained from your Shell representative.