



# Shell ROTELLA® T5 15W-40

- Low Emissions
- Better Low Temperature Flow

## Premium Synthetic Blend Technology – Heavy duty diesel engine oil

Shell ROTELLA® T5 premium synthetic blend heavy duty engine oil with Triple Protection Plus™ technology has been enhanced with premium synthetic base oils plus advanced additive technology to protect against wear, deposits and oil breakdown PLUS better low temperature flow and extended drain capabilities\*.



### Performance, Features & Benefits

Shell ROTELLA® T5 premium synthetic blend heavy duty engine oil with Triple Protection Plus™ technology has been enhanced with premium synthetic base oils plus advanced additive technology to protect against wear, deposits and oil breakdown PLUS better low temperature flow and extended drain capabilities\*.

- **Emissions system compatibility**

Advanced low-ash formulation helps control the blocking or poisoning of exhaust after-treatment devices, helping maintain vehicle emission compliance and engine fuel efficiency.

- **Premium Synthetic Blend**

The use of premium synthetic base oil components provides Shell ROTELLA® T5 synthetic blend with the capability to improve cold starting and low temperature performance, without compromising engine protection or durability.

- **Improved engine cleanliness**

The advanced formulation delivers good engine cleanliness and protection against piston deposits ensuring engine and component reliability at extended oil drain intervals.

- **Low emission engine use**

Shell ROTELLA® T5 meets the requirements of the major North American engine manufacturers for low emission applications.

### Main Applications



### Specifications, Approvals & Recommendations

- API CK-4, CJ-4
- ACEA E9
- Allison TES-439
- Caterpillar ECF-3, ECF-2
- Cummins CES 20086, 20081
- Detroit Fluid Specification (DFS) 93K222, 93K218
- Deutz DQC III-18 LA
- Ford WSS-M2C171-F1
- MACK EOS-4.5, EO-O Premium Plus
- MAN 3775
- MB Approval 228.31
- MTU Category 2.1
- Volvo VDS-4.5, VDS-4

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk

### Typical Physical Characteristics

Properties			Method	Shell ROTELLA T5 15W-40
Kinematic Viscosity	@ 40°C	mm <sup>2</sup> /s	ASTM D445	111.2
Kinematic Viscosity	@ 100°C	mm <sup>2</sup> /s	ASTM D445	14.9
Dynamic Viscosity	@ -20°C	mPa s	ASTM D5293	6 200

Properties		Method	Shell ROTELLA T5 15W-40
Viscosity Index		ASTM D2270	138
Total Base Number	mgKOH/g	ASTM D2896	8.5
Sulphated Ash	%	ASTM D874	1.0
Density	@ 15°C kg/l	ASTM D4052	0.866
Flash Point (COC)	°C	ASTM D92	251
Pour Point	°C	ASTM D97	-37

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

## Health, Safety & Environment

### • Health and Safety

Shell ROTELLA® T5 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

### • Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

## Additional Information

### • Advice

Advice on applications not covered here may be obtained from your Shell representative.

\* Compared to conventional SAW 15W-40.