

OILPRO FULL SYN LS GEAR OILS

PREMIUM SYNTHETIC LIMITED SLIP GEAR LUBRICANTS

SAE GRADES: 75W-90, 75W-140 & 80W-140



PRODUCT DESCRIPTION

OILPRO Full Synthetic MP LS Gear Oils are designed to provide superb performance for automobiles, light and heavy duty trucks, and various industrial equipment when API Service Classification GL-5 and MT-1 is specified. The products are compounded with synthetic base stocks that have outstanding thermal stability and resistant to high temperature oxidation. The additive system provides extreme pressure characteristics, anti-wear performance, anti-corrosion inhibition, rust prevention, and anti-foaming tendencies.

PRODUCT APPLICATION

Recommended for differentials, rear axles, final drives, conventional manual transmissions, manual steering gears in passenger cars and trucks where API GL-5 type lubricant is specified for severe service and long life. Recommended for gear applications where a controlled sulfur/phosphorus additive package is designated or preferred and extreme cold operating conditions are encountered. Complies with API MT-1 capability for non synchronized manual transmissions in heavy duty systems. Meets the performance requirements of U.S. Military Specification MIL-PRF-2105E, Eaton Axle PS-037, PS-163, PS-109(75W-90)/Dana Drive Axle (E500 Roadranger) SHAES-256 Rev. C, Mack GO-J PLUS(75W-90) and GO-J(80W-140).



TYPICAL TECHNICAL PROPERTIES

PROPERTY	75W-90	75W-140	80W-140
Viscosity @ 40°C (cSt)	102.7	194.75	207.5
Viscosity @ 100°C (cSt)	15.5	27.3	25.5
Viscosity Index	160	178	155
API Gravity @ 60°F	30.0	33.9	30.0
Flash Point °C (°F)	221 (430)	227 (440)	227 (440)
Pour Point °C (°F)	-48 (-55)	-46 (-50)	-46 (-50)



This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap & water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. SUPPLYPRO, LLC assumes no responsibility for product misuse or improper application. For a copy of this product's Safety

Data Sheet (SDS) or Technical Data Sheet (TDS), visit

www.SUPPLYPRO1.com



SUPPLYPRO, INC | 115 Empire Way SW, Atlanta, GA 30354 | www.supplypro1.com



FEATURES AND BENEFITS

OILPRO FULLSYN LS GEAR OILS - 75W-90 GL-5, 75W-140 GL-5 & 80W-140 GL-5 - feature technologically advanced additive chemistry to provide extended performance under even the most severe operating conditions that often occur in today's modern gear systems:

- Provides excellent protection against wear produced by high torque found in today's modern gear units.
- Protects gear and bearing metals from scuffing and welding.
- Resists thermal breakdown even under extreme operating conditions in cold or hot weather.



PRODUCT NUMBERS

SAE GRADE	PACKAGE SIZE	PRODUCT #
75W-90	BULK	01205105975W90116
75W-90	DRUM	01205105975W90089
75W-90	PAIL	01205105975W90081
75W-90	KEG	01205105975W90100
75W-90	6/1 QT	01205105975W90129
75W-140	BULK	01205205975140116
75W-140	DRUM	01205205975140089
75W-140	PAIL	01205205975140170
75W-140	KEG	01205205975140100
75W-140	4/1 GAL	01205205975140124
75W-140	6/1 QT	01205205975140129
80W-140	BULK	01205205980140116
80W-140	DRUM	01205205980140089
80W-140	PAIL	01205205980140160
80W-140	KEG	01205205980140100