

OILPRO FULL SYNTHETIC MULTI-VEHICLE ATF

PREMIUM FULL SYNTHETIC MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID



PRODUCT DESCRIPTION

OILPRO FULL SYNTHETIC MULTI-VEHICLE ATF is a full synthetic universal automatic transmission fluid specifically designed for passenger car and light duty trucks to meet the performance requirements and suitability for use in the vast majority of today's modern Fuel Efficient transmissions (6 or more speeds). Its performance features can also be realized in the majority of older transmission applications (<6 speeds).

FEATURES AND BENEFITS

- Lower inventory cost; one ATF can be used for a vast majority of Automatic Transmissions on the road today.
- Longer equipment life; specially formulated for extra wear control, corrosion protection formation of lacquers, sludge or other harmful deposits.
- JASO 1A Anti Shudder Durability (ASD) Performance
- Designed for modern fuel efficient transmissions as well as older transmissions
- Designed for longer fluid life & faster oil flow in low temperature operation.
- Consistent shift quality throughout the life of the fluid.
- Improved performance vs. Dexron® III :
 - Friction Stability
 - Oxidation Resistance
 - Wear Control
 - Clutch Durability
 - Foaming Resistance
 - Corrosion Control
- Frictions modifiers control lock-up rates of clutch packs for proper transmission shifting characteristics and efficient power transfer.
- Controls seal deterioration to limit fluid leakage.
- Multi-graded for optimum performance during cold starts and high temperature operations, including start/stop severe service.



TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	ADVANCED MV ATF
Kinematic Viscosity		
@ 40°C (cSt)	ASTM D445	29.3
@ 100°C (cSt)	ASTM D445	5.9
Viscosity Index	ASTM D2270	151
Brookfield Viscosity, cPs @ -40°C	ASTM D2983	10,800 cP
API Gravity	ASTM D4052	34.2
Flash Point °C		221 °C
Pour Point °C	ASTM D97	< -46°C

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap & water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. SUPPLYPRO, LLC assumes no responsibility for product misuse or improper application.

For a copy of this product's Safety Data Sheet (SDS) or Technical Data Sheet (TDS), visit www.SUPPLYPRO1.com

FULL SYNTHETIC AUTOMATIC TRANSMISSION FLUID

PRODUCT APPLICATIONS

- BMW/Mini
- Chrysler/Dodge/Jeep
- Ford/Mazda
- General Motors
- Honda
- Hyundai
- Idemitsu
- Isuzu
- Jaguar
- KIA
- Land Rover
- Mitsubishi
- Nissan/Infiniti
- Porsche
- SAAB
- Toyota/Lexus
- Subaru
- Suzuki
- Volvo
- VW/Audi

* Specific applications on page 2.



OILPRO ADVANCED FULL SYN MV ATF

PREMIUM FULL SYNTHETIC MULTI-VEHICLE
AUTOMATIC TRANSMISSION FLUID



SPECIFICATIONS

Acura ATF-Z1	Chrysler/Dodge/Jeep 68157995AB, 68218925AA	Jaguar ATF 3403 M115, ATF 3403-M115, LT71141	Porsche 000 043 205 28, Z 000169756
Aisin Warner JWS 3309(T-IV), 3324(WS), AW-1	Daewoo LT 71141	Jaguar JLM 20292, Fluid 8432, 02JDE26444	Porsche ATF 3403-M115
Allison C-3, C-4	Daihatsu AMMIX ATF D-II, AMMIX ATF D-III SP	Jaguar JLM WSS-M2C922A1	Porsche T-IV (JWS 3309)
American Motors ATF +3 (MS7176-E)	Esso LT 71141	Jaguar ZF 5HP24, JLM20238	Porsche ZF 5HP19FL, ZF 5HP20, LT71141
ATF RED1, RED 1K	FIAT T-IV type, JWS 3309	Jaguar ZF ATF 3403 JLM20238, K17	Renault DPO/AL4, Matic D2, Samsung SATF-D
Audi 5 HP LT71141 (ZF 5HP 18FL/19FL/24A)	Ford ESP-M2C166H, XL-12	JASO M315-2013 1A, 1A-LV, 2A	Saab T-IV (JWS 3309), 93 165 147, 93 160 393
Audi/VW G 052 025-A2, G 053 025-A2	Ford FNR5 (Mazda M5, XT-9-QMM5)	Jeep ATF+3	Saturn T-IV (JWS 3309)
Audi/VW G 052 162-A1/A2, G 055 025 A2	Ford MERC LV (FF-WSS-M2C-938A/SF, XT-10 QLV)	KIA ATF SP-II, SP-III, SP-IV, SP-IVM, Red 1	Scion (all vehicles)
Audi/VW (JWS 3309)	Ford MERC, MERC SP, MERC V	Land Rover LR023288, TYK500050, LR0022460	Shell 3403, M115, LA2634, L12108,M-1375.4, 3353
Audi/VW G 052 990, G 055 540 (A2), G 052 055	Ford WSS M2C 138CJ, 166H	Lexus JWS 3309	Ssang yong DSIH 5M-66
Audi/VW G 052-162 (ZF lifeguard fluid 5)	Ford WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309	MAN 339A, Type D, Type F, Z1, Z2, V1, V2	Subaru ATF, K0140Y0700, ATF 5AT
Audi/VW (ZF No. S671 090 170)	Ford/Lincoln/Mercury XT-2-QDX (M), XT-2QSM (Syn)	Maserati 231603	Subaru DEX -II, ATF, ATF HP
Audi/VW G 055 055-A, G 055 162-A2	Ford/Lincoln/Mercury XT-6-QSP OR -DSP (SP)	Mazda ATF D-II, ATF M-III, ATF M-V	Suzuki ATF 2384K, JWS 3309, ATF 3314, ATF 3317
Audi/VW A2(ZF Lifeguardfluid 6)	Fuso ATF-II, Fuso ATF SPII, Fuso ATF-A4	Mazda ATF FZ, ATF F-1, ATF S-1	Suzuki ATF AW-1, AT OIL 5D06, ATF 2326
Audi/VW (ZF No. S671 090 255)	GM 1940700, 1940767, 21005966, 22717466	Mercedes Benz ZF 4HP20, 236.1, .2, .3, .5	Texaco 7045-E, 8072B, N402
Audi/VW A6 (ZF Lifeguardfluid 6 Plus)	GM 88900925, 9986195, 93160393	Mercedes Benz 236.6, 236.7, 236.8, 236.9	Toyota ATF D-II, D-III, T-III, T-IV, WS, Hybrid
Audi/VW (ZF No. S671 090 281)	GM DEX -II, -IID, -IIE, -IIIG, -IIIH, -VI	Mercedes Benz 236.10, 236.11, 236.12, 236.41	Vickers M2950-S, I-286-S
Audi/VW G 060 162 (ZF Lifeguardfluid 8)	GM TASA	Mini Cooper T-IV	Voith 55.6335.xx (G607), 55.6336.xx (G13636)
Audi/VW (ZF No. S671 090 312)	GM/GMC/Saturn AW1, VI, 88863400, 88863401	Mitsubishi Diaqueen AW, J2, J3, ATF-MA1 ATF PA	Voith Svc Bln #013 and #118
Bentley PY112995PA	GM9986195(Aisin AW, JWS 3309)	Mitsubishi Diaqueen SK, SP-II, SP-III, SP-IV	Volvo 97325, 97335, CE 97340, CE 97342
BMW JWS 3309 (T-IV), LA2634, , BMW MINI	Hino Blue ribbon ATF	NAG 1 (Chrysler, Jeep, Cherokee), NAG 2 (Chrysler)	Volvo PN 1161521, PN 1161540/1161640
BMW LT71141 (ZF 5HP 18FL/19FL/24A), ETL8072B	Honda ATF-Z1 (except in CVT's), ATF Ultra II	Nissan Matic Fluid C, D, J, K, S	Volvo PN 31256774/PN 31256675, PN 1161621
BMW ZF 5HP18FL, 5HP24, 5HP30, 7045E	Honda DW-1, Type 3.0, Type 3.1	Opel/GM 19 40 700, 19 40 767	VW 5 HP (ZF 5HP 30), (18FL, 30), (19FL, 24A)
Bosch TE-ML 09	Hyundai/Kia 040000C90SG, NUMM040 CH20 Red-1	Opel/GM 21005966 Transaxle, 22 17466	VW G US 000 162
CAT TO-2	Hyundai/Kia Dex-II/SP-II, JWS 3314, NWS 9638	Opel/GM 88900925, 9986195	VW TL 521 62
Chrysler, +2, +3 (MS 7176E), +4	Hyundai/Kia SP-IV (00232-1904/04500-00115)	Peugeot ZF 4HP20	ZF 8 speed transmissions, 9 speed transmissions
Chrysler/Dodge MOPAR AS 68 RC	Hyundai/Kia SP-IV M (SP4-M), SPH-IV	Peugeot/Citreon (PSA) AL4 AutomaticGearboxoil	ZF all 3 & 4 speed transmission
Chrysler/Dodge AS 69 RC (T-IV), JWS 3309	Hyundai/Kia SP-IV-RR, SP-III	Peugeot/Citreon (#9730.AE)	ZF TE-ML 04D,14A, 14B, 16L, 17C
Chrysler/Dodge/Jeep 05127382AA, 68043742AA	Idemitsu K17 3100 PLO85	Peugeot/Citreon Z 000169756	ZF TE-ML 05L, 09, 11A, 11B, 21L, 02F, 03D
Chrysler/Dodge/Jeep 68157995AA, 68171866AA	ISUZU BESCO ATF-II, III, SP, SCS Fluid, 08200-9001	Porsche 000 043 205 09, 999 917 547 00 (A2)	ZF TE-ML 21L, ZF TE-ML 02F, ZF TE-ML 03D

PRODUCT NUMBERS

FULL SYNTHETIC MULTI-VEHICLE ATF	
BULK	00900401200ATF116
55G DRUM	00900401200ATF089
5G PAIL	00900401200ATF177
12/1 QT	00900401200ATF035



This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap & water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. SUPPLYPRO, LLC assumes no responsibility for product misuse or improper application.

For a copy of this product's Safety Data Sheet (SDS) or Technical Data Sheet (TDS), visit www.SUPPLYPRO1.com



SUPPLYPRO, LLC | 115 Empire Way, Atlanta, GA 30354 | www.supplypro1.com